



COMMON AREA SIGN NOTES

- 1) INSTALL SIGN DISPLAYING INTERNATIONAL SYMBOL OF ACCESSIBILITY @ 60" A.F.F. AT EACH BUILDING ENTRANCE.
- 2) PROVIDE TACTILE SIGN WITH THE WORDS "COMMUNITY BUILDING" 60" A.F.F. ON THE LATCH SIDE OF THE DOOR SHOWN.
- 3) PROVIDE SIGN STATING "FIRE ALARM CONTROL PANEL" (VERIFY EXACT WORDING AND LOCATION WITH CITY OF VALLEJO FIRE DEPARTMENT)
- 4) PROVIDE SIGN WITH THE WORDS "UTILITY ROOM" @ 60" A.F.F. ON THE LATCH SIDE OF THE DOOR.
- 5) PROVIDE TACTILE EXIT SIGN WITH THE WORDS "EXIT" @ 60" A.F.F. ON THE WALL ADJACENT TO THE LATCH SIDE OF A SINGLE-LEAF DOOR OR ON THE ADJACENT RIGHT WALL OF A DOUBLE-LEAF DOOR (CBC 10011.3, CBC 11178.8.7)
- 6) PROVIDE TACTILE SIGN WITH THE WORDS "UTILITY ROOM" @ 60" A.F.F. ON THE LATCH SIDE OF THE DOOR.
- 7) PROVIDE TACTILE SIGN WITH THE WORDS "MEN" 60" A.F.F. ON THE LATCH SIDE OF THE DOOR SHOWN. SEE DOOR SCHEDULE FOR ADDITIONAL REQUIREMENTS.
- 8) PROVIDE TACTILE SIGN WITH THE WORDS "WOMEN" 60" A.F.F. ON THE LATCH SIDE OF THE DOOR SHOWN. SEE DOOR SCHEDULE FOR ADDITIONAL REQUIREMENTS.
- 9) PROVIDE SIGN WITH THE WORDS "STORAGE" 60" A.F.F. ON THE LATCH SIDE OF THE DOOR.
- 10) PROVIDE SIGN WITH THE WORDS "BUSINESS CENTER" 60" A.F.F. ON THE LATCH SIDE OF THE DOOR.
- 11) PROVIDE SIGN WITH THE WORDS "STORAGE / COPY" 60" A.F.F. ON THE LATCH SIDE OF THE DOOR.
- 12) PROVIDE SIGN WITH THE WORDS "OFFICE 1" 60" A.F.F. ON THE LATCH SIDE OF THE DOOR.
- 13) PROVIDE SIGN WITH THE WORDS "OFFICE 2" 60" A.F.F. ON THE LATCH SIDE OF THE DOOR.
- 14) PROVIDE SIGN WITH THE WORDS "FITNESS" 60" A.F.F. ON THE LATCH SIDE OF THE DOOR.
- 15) PROVIDE SIGN WITH THE WORDS "KITCHEN" 60" A.F.F. ON THE LATCH SIDE OF THE DOOR.
- 16) PROVIDE SIGN WITH THE WORDS "LL SCIENCE PROJECT" THE LATCH SIDE OF THE DOOR.

KEYNOTES

- METAL FENCE GAS METER ENCLOSURE. SEE NORTH ELEVATION
- LIGHTING CONTROL PANEL. SEE ELECTRICAL DRAWINGS
- SEE E ELECTRICAL DWSG FOR TELEPHONE PANEL LOCATION
- FIRE SPRINKLER RISER
- WATER HEATER. SEE MECH. DWSGS
- SEE MECHANICAL DWSGS. FOR HVAC UNITS
- CONDENSER
- PAIR 2'-0" WIDE X 6' HIGH METAL GATES
- HANDICAPPED ACCESSIBLE DRINKING FOUNTAIN. PROVIDE HIGH AND LOW DRINKING FOUNTAIN
- DOUBLE SINK AND GARBAGE DISPOSAL. COMPLY WITH CBD 1115B.4.7(2)
- DISHWASHER
- RANGE AND OVEN
- REFRIGERATOR WITH WATER SUPPLY FOR ICEMAKER
- 30" MIN CLR. SPACE BELOW COUNTER
- MICROWAVE
- RANGE HOOD, AND FAN. MOUNT CONTROLS AT 44" ABOVE FIN. FLR.
- BASE CABINETS
- UPPER CABINETS
- 60" DIAMETER FOR ADA ACCESS
- COUNTER
- HOLES FOR DATA CABLES
- COPIER LOCATION
- FILE CABINET LOCATION
- RECESSED FIRE EXTINGUISHER (PORTABLE) - TYPICAL ONE 2A-10BC TYPE AT LOCATIONS SHOWN
- ADJUSTABLE OPEN SHELVES
- TV/VIDEO GAME SPACE
- FIRE DEPARTMENT KNOX BOX.
- not used
- WOOD TRELLIS
- 8' WALL MOUNTED MIRROR
- ROOF DOWNSPOUTS
- FABRIC AWNING
- 6' HIGH WOOD FENCE SEE DETAIL SHEET A9.4
- 16X16 WALL LONERS IN AT 12' ABOVE FLR. 12" BELOW

TACTILE EXIT SIGN DETAILS

THE MINIMUM CHARACTER HEIGHT SHALL BE 5/8"
PLUS $\frac{1}{6}$ " PER FOOT OF VENING DISTANCE ABOVE 72"



X = 2 prong outlet
* = 4 " " "
● = Basic Cable
C = CAT5 cable
SC = Security Camera

GENERAL NOTES

- ALL DIMENSIONS ARE TO FACE OF STUD OR CENTERLINE OF PARTITION WALL, INTERIOR COLUMN/ WINDOW/ DOOR UNLESS OTHERWISE NOTED.
- DETAILS ARE KEYED AND NOTED TYPICAL ONLY ONCE ON THE PLANS WHEN THEY FIRST OCCUR, AND ARE REPRESENTATIVE OF SIMILAR CONDITIONS THROUGHOUT, UNLESS OTHERWISE NOTED.
- PROVIDE WATER-RESISTANT GYP. BOARD AT ALL WET WALL LOCATIONS.
- FOR DOOR AND WINDOW KEYS REFER TO DOOR AND WINDOW SCHEDULE. SEE A9.1
- REFER TO INTERIOR ELEVATION FOR CABINETS CALLOUTS. SEE SHEET A2.3, A2.4 & A2.5.
- FOR ALL TOILETS ACCESSORIES & HEIGHTS REFER TO A2.3, A2.4 & A2.5
- FOR FINISH FLOOR REFER TO FINISH SCHEDULE A4.1.
- PROVIDE ACOUSTICAL SEALANT AT ALL WALLS AND CEILING CONDITION.
- PROVIDE 5/8" THIC. GYP. BD. MOISTURE RESISTANT AT WET AREAS , BATHROOMS & KITCHEN SINK AREA.
- PROVIDE WD. BLOCKING BEHIND GYPSUM BD. PARTITION FOR ATTACHMENT FOR ALL FIXTURE, FITTINGS, ART WORK & ACCESSORIES.
- PROVIDE WD. BLOCKING AT CEILING FOR BLINDS AT WINDOW WHERE REQUIRED.
- GROUND AND FLOOR SURFACES AT ACCESSIBLE ROUTES TO BE SLIP RESISTANCE PER CBC 124.6
- SLOPE FLOOR DRAIN $\frac{1}{4}$ "=1'-0 SEE PLUMBING DWGS.
- PROVIDE WD. BLOCKING IN WALL AT GRAB BAR, CABINETS, SHELVES, AND CEILINGS AS REQUIRED FOR WINDOW SHADING.
- PLYWOOD SHEAR WALL TO EXTEND FULL HEIGHT OF THE WALL SSD.
- INTERIOR FINISHES CEILINGS & WALLS SHALL BE CLASSIFIED W/ASTME 84-TYPE "C" FLAMED SPREAD 76-203, SMOKE DEVELOPED AT 0-450. TESTED W/NFPA 286
- INTERIOR TRIM SHALL HAVE A MIN. CLASS C FLAMED SPREAD & SMOKE DEVELOP INDEX WHEN TESTED W/ASTME-84 AND NOT TO EXCEED 10% OF AGGREGATE WALL OR CLG.

EGEND

Architectural drawing showing a wall section with three callouts. The first callout, pointing to the left, is labeled 'ONE HOUR RATED WALL SEE DETAIL SHEET X/XK'. The second callout, pointing to the right, is labeled 'INTERIOR FULL HT. PARTITION SEE DETAIL SHEET XXX'. The third callout, pointing to the right, is labeled 'INTERIOR BEARING PARTITION WALL SEE DETAIL SHEET XXX'. Below the wall section, a callout points to a circular fire extinguisher icon with the label 'FIRE EXTINGUISHER'.

DRAWINGS FOR REVIEW AND
BIDDING PURPOSES ONLY-NOT
FOR CONSTRUCTION. SUBMIT RFI
FOR CONFLICTS OR INFORMATION
NOT SHOWN



REVISIONS	BY
2011 - PLAN CHECK	G.O.
1/2013 - GAS METER	STAFF
2014 BIDDING	STAFF
NEW, DOOR MARKS ADDED	
NEW, DOOR MARKS ADDED	
ADDED - FLOR FINISHES	
ADDED	
	
OAKLEY & OAKLEY <small>ARCHITECTURAL & STRUCTURAL ENGINEERS</small> 7700 FOREWATER DRIVE STE 615 SAN ANGELO, TX 76904-1294 TEL 325.652.6643	

COMMUNITY CENTER
ARBOR PARK APARTMENTS
9 PORTER STREET, VALLEJO, CA 94560
HOME INC.

FIRST FLOOR PLAN

FIRS
HOME

08/30/2011
AS NOTED
STAFF
RY
2011-09

A2.1